

### V1206-PD Zero Client TERA2 PColP® Portal Processor

Model Numbers: V1206-PD

## Industry Leading Endpoint for VMware and Amazon Workspaces

The 10ZiG V1206-PD is part of our V1200 Tera2 PColP® Zero Client Series optimized for VMware and Amazon WorkSpaces environments. With no operating system and no local storage, the V1200 Series line provides an ultra-secure, yet powerful and easy-to-manage endpoint that eliminates the chance of viruses and provides extensive USB security and authentication features. Options ranging from dual through quad screen, PoE, Fiber, DVI-I, DVI-D, 4 DisplayPort and Internal Smart Card (CAC) with up to 6 USB 2.0 ports, as well as standard TAA Compliance.

The V1206-PD model highlighted below supports dual screens and comes equipped with 1 x DisplayPort and 1 x DVI-I and 6 x USB 2.0 along with a Fiber option. All V1200 Series PColP® Zero Clients by 10ZiG receive one year free of the Desktop Access Subscription. The Desktop Access Subscription includes the PColP Management Console with a subscription to firmware and security updates as well as tech support.



- ▶ TERA2 PColP Portal Processor, Tera 2321 PColP Chipset
- ▶ 1 x DisplayPort + 1 x DVI-I
- ▶ 6 x USB 2.0
- ▶ Optional Fiber Support (SFP Ready)
- ▶ TAA Compliant
- ▶ Optional VESA Mount
- ▶ 1 year free of Desktop Access Subscription

# V1206-PD Zero Client

## Tera2 PCoIP Zero Client Series



### SPECIFICATIONS

1. Power Button/Power LED
2. USB 2.0 (4)
3. Line Out
4. Mic In
5. USB 2.0 (2)
6. RJ45 LAN Port (optional SFP Ready)
7. DVI-I
8. DisplayPort
9. DC Jack
10. Kensington Lock

System Specifications	
Management Utility	PCoIP Management
Processor	PCoIP® Portal Processor - TERA2
Chipset	TERA2321 PCoIP®
Dimensions	
Device	5.21" (D) x 1.06" (W) x 6.77" (H) - 132mm x 27mm x 172mm
Weight	2.53lbs (1.15kgs)
Connections	
Ports	6 x USB 2.0, 1 x Mic In, 2 x Line Out
Video/Resolution	1 Monitor at 2560 x 1600 or 2 Monitors at 1920 x 1200, 1 x DisplayPort + 1 x DVI-I
Networking	
Ethernet	10/100/1000 Base-T
Fiber	Optional SFP Fiber Connector (100/1000Mbps)
Environmental	
Operating Temp.	32-104F (10-40C) 10-90% non-condensing humidity
Power	8 Watts, DC-12V/3A External Power Adapter
Certifications	
CE, FCC, CAN ICES-3/NMB-3, VCCI, UL, TUV-GS, C-Tick, GOST, BSMI, RoHS	



Americas  
EMEA  
APAC  
DE

P: +1 (866) 865-5250  
P: +44 (0) 116 214 8650  
P: +61 2 80027421  
P: +49 (0) 6724 9304-45

E: info@10ZiG.com  
E: info@10ZiG.eu  
E: info@10ZiG.com.au  
E: vertrieb@10zig.de

W: www.10ZiG.com

