

### V1206-P Zero Client Tera2 PCoIP® Portal Processor

Model Numbers: V1206-P

## Industry Leading Endpoint for VMware and Amazon Workspaces

The 10ZiG V1206-P is part of our V1200 Tera2 PCoIP® Zero Client Series optimized for VMware and Amazon WorkSpaces environments. With no operating system and no local storage, the V1200 Series line provides an ultra-secure, yet powerful and easy-to-manage endpoint that eliminates the chance of viruses and provides extensive USB security and authentication features. Options ranging from dual through quad screen, PoE, Fiber, DVI-I, DVI-D, 4 DisplayPort and Internal Smart Card (CAC) with up to 6 USB 2.0 ports, as well as standard TAA Compliance.

The V1206-P model highlighted below supports dual screens and comes equipped with 2 x DVI-I and 6 x USB 2.0 along with a Fiber option. All V1200 Series PCoIP® Zero Clients by 10ZiG receive one year free of the Desktop Access Subscription. The Desktop Access Subscription includes the PCoIP Management Console with a subscription to firmware and security updates as well as tech support.



▶ TERA2 Portal Processor, Tera2321 PCoIP Chipset
▶ 2 x DVI (1 x DVI-I, 1 x DVI-D)
▶ 6 x USB 2.0
▶ Optional Fiber Support (SFP Ready)
▶ TAA Compliant
▶ Optional VESA Mount
▶ 1 year free of Desktop Access Subscription

# V1206-P Zero Client

## Tera2 PCoIP Zero Client Series



### SPECIFICATIONS

1. Power Button/Power LED
2. USB 2.0 (4)
3. Line In
4. Mic Out
5. USB 2.0 (2)
6. RJ45 LAN Port (optional SFP Ready)
7. DVI-D
8. DVI-I
9. Rear Line Out
10. Kensington Lock
11. DC Jack

System Specifications	
Management Utility	PCoIP Management
Processor	PCoIP® Portal Processor - TERA2
Chipset	TERA2321 PCoIP®
Dimensions	
Device	5.2" (D) x 1.7" (W) x 6.3" (H) - 134mm x 43mm x 160mm
Weight	1.5lbs (0.68kgs)
Connections	
Ports	6 x USB 2.0, 1 x Mic In, 2 x Line Out
Video/Resolution	1 Monitor at 2560 x 1600 or 2 Monitors at 1920 x 1200, 1 x DVI-D + 1 x DVI-I
Networking	
Ethernet	10/100/1000 Base-T
Fiber	Optional SFP Fiber Connector (100/1000Mbps)
Environmental	
Operating Temp.	50-104F (10-40C) 10-95% non-condensing humidity
Power	6 Watts, DC-12V/3A External Power Adapter
Certifications	
CE, FCC, CAN ICES-3/NMB-3, VCCI, UL, TUV-GS, C-Tick, GOST, BSMI, RoHS	



Americas  
EMEA  
APAC  
DE

P: +1 (866) 865-5250  
P: +44 (0) 116 214 8650  
P: +61 2 80027421  
P: +49 (0) 6724 9304-45

E: info@10ZiG.com  
E: info@10ZiG.eu  
E: info@10ZiG.com.au  
E: vertrieb@10zig.de

W: www.10ZiG.com

